

MOTIVATION THROUGH INNOVATION™



Head office address: Global House, Hall Lane, Dereham, NR20 3GG

UK central sales line:

Tel: 0845 555 55 11 | Fax: 0845 555 55 22 | sales@strident.uk.com

Northern office:

Tel: +44 (0)1302 365987 | Fax: +44 (0)1302 365988

Southern office:

Tel: +44 (0)1362 300102 | Fax: +44 (0)1362 300103

www.strident.uk.com

All specifications correct at the time of publishing.

In line with our policy of continual product development, we reserve the right to change product specifications without prior notice.

Literature Code: IV4/2016MB

© Ivanhoe Trading Limited 2016

Mobility Battery Catalogue 2016-2017

Mobility Battery Catalogue

2016-2017

Strident - a name you can trust for performance and reliability

A careful selection of only the highest quality raw materials, consistent quality control throughout the entire production process and painstaking attention to every detail gives the Strident range its unique properties that can be trusted and relied upon in many vital applications.

Valve Regulated

The highest specification of valve equipment is used in the Strident brand to allow the required level of venting both in use and more importantly during the charge process.

Quality Assured

Every Strident battery undergoes stringent quality control both at manufacture stage and pre-despatch ensuring you receive only the most reliable source of power. Our highly automated central UK warehousing facilities operates a strict FIFO stock rotation system resulting in all goods despatched being in peak condition every time.

Plate Separator

A critical component to high performing batteries. Strident use superior glass matting to ensure consistent plate contact resulting in increased battery efficiency and longevity.

Plate Composition

Purified lead specifically blended with critical conductive properties gives the Strident range superior performance during both cyclic and standby applications.



With over 15 years experience in the mobility industry, Strident are perfectly placed to offer the widest range of high quality mobility consumables including mobility tyres, batteries and chargers.

All Strident batteries are designed and manufactured to ensure they meet the stringent quality control standards that all Strident products must adhere to.

Only products that demonstrate a proven high level of performance and integrity become part of the Strident range of mobility products and accessories.

Our range of AGM, GEL and Small Cell batteries offer excellent longevity and reliability. This comprehensive range is suitable for a wide range of mobility scooters and equipment.

Please contact our sales team to find out more about the full Strident mobility range of products.

UK central sales line:
Tel: 0845 555 55 11 | Fax: 0845 555 55 22 | sales@strident.uk.com
www.strident.uk.com



Contents



AGM Batteries 4

GEL Batteries 6

Terminal Adaptors 7

Small Cell Batteries 7



AGM Batteries

STRIDENT
- +



Voltage & Capacity: 6V 1.2Ah
Dimensions mm (L x w x h): 97 x 24 x 52
Total Height mm: 58
Quantity/Ctn: 20

Terminal: F1



Voltage & Capacity: 6V 12Ah
Dimensions mm (L x w x h): 151 x 50 x 94
Total Height mm: 100
Quantity/Ctn: 10

Terminal: F1



Voltage & Capacity: 12V 0.8Ah
Dimensions mm (L x w x h): 96 x 25 x 61.5
Total Height mm: 61.5

Terminal: VHR-2N



Voltage & Capacity: 12V 1.2Ah
Dimensions mm (L x w x h): 97 x 43 x 52
Total Height mm: 58
Quantity/Ctn: 20

Terminal: F1



Voltage & Capacity: 12V 2.3Ah
Dimensions mm (L x w x h): 178 x 35 x 61
Total Height mm: 67
Quantity/Ctn: 10

Terminal: F1



Voltage & Capacity: 12V 2.3Ah
Dimensions mm (L x w x h): 182 x 24 x 61
Total Height mm: 61
Quantity/Ctn: 10

Side Contact



Voltage & Capacity: 12V 2.6Ah
Dimensions mm (L x w x h): 178 x 35 x 61
Total Height mm: 67
Quantity/Ctn: 10

Terminal: F1



Voltage & Capacity: 12V 2.9Ah
Dimensions mm (L x w x h): 79 x 56 x 99
Total Height mm: 104
Quantity/Ctn: 10

Terminal: F1



Voltage & Capacity: 12V 3.2Ah
Dimensions mm (L x w x h): 134 x 67 x 61
Total Height mm: 67
Quantity/Ctn: 10

Terminal: F1



Voltage & Capacity: 12V 4Ah
Dimensions mm (L x w x h): 195 x 47 x 71
Total Height mm: 76
Quantity/Ctn: 10

Terminal: F1



Voltage & Capacity: 12V 5Ah
Dimensions mm (L x w x h): 90 x 70 x 101
Total Height mm: 107
Quantity/Ctn: 10

Terminal: F1



Voltage & Capacity: 12V 7Ah
Dimensions mm (L x w x h): 151 x 65 x 95
Total Height mm: 101
Quantity/Ctn: 8

Terminal: F1



AGM Batteries

STRIDENT
- +



Voltage & Capacity: 12V 7Ah Fire Retardant
Dimensions mm (L x w x h): 151 x 65 x 95
Total Height mm: 101
Quantity/Ctn: 8

Terminal: F1



Voltage & Capacity: 12V 9Ah
Dimensions mm (L x w x h): 151 x 65 x 95
Total Height mm: 101
Quantity/Ctn: 8

Terminal: F2



Voltage & Capacity: 12V 10Ah
Dimensions mm (L x w x h): 151 x 65 x 111
Total Height mm: 117
Quantity/Ctn: 5

Terminal: F2



Voltage & Capacity: 12V 12Ah
Dimensions mm (L x w x h): 151 x 98 x 95
Total Height mm: 101
Quantity/Ctn: 4

Terminal: F2



Voltage & Capacity: 12V 14Ah
Dimensions mm (L x w x h): 151 x 98 x 95
Total Height mm: 101
Quantity/Ctn: 4

Terminal: F2



Voltage & Capacity: 12V 20Ah
Dimensions mm (L x w x h): 181 x 77 x 167
Total Height mm: 167
Quantity/Ctn: 2

Terminal: Insert M5



Voltage & Capacity: 12V 25Ah
Dimensions mm (L x w x h): 166 x 175 x 125
Total Height mm: 125
Quantity/Ctn: 2

Terminal: Insert M5



Voltage & Capacity: 12V 34Ah
Dimensions mm (L x w x h): 197 x 131 x 159
Total Height mm: 168
Quantity/Ctn: 2

Terminal: Insert M6



Voltage & Capacity: 12V 36Ah
Dimensions mm (L x w x h): 197 x 131 x 155
Total Height mm: 168
Quantity/Ctn: 2

Terminal: Insert M6



Voltage & Capacity: 12V 42Ah
Dimensions mm (L x w x h): 198 x 166 x 170
Total Height mm: 170
Quantity/Ctn: 1

Terminal: Insert M6



Voltage & Capacity: 12V 45Ah
Dimensions mm (L x w x h): 198 x 166 x 170
Total Height mm: 170
Quantity/Ctn: 1

Terminal: Insert M6



Voltage & Capacity: 12V 50Ah
Dimensions mm (L x w x h): 198 x 166 x 170
Total Height mm: 170
Quantity/Ctn: 1

Terminal: Insert M6



UK central sales line:
Tel: 0845 555 55 11 | Fax: 0845 555 55 22 | sales@strident.uk.com
www.strident.uk.com

UK central sales line:
Tel: 0845 555 55 11 | Fax: 0845 555 55 22 | sales@strident.uk.com
www.strident.uk.com



AGM Batteries

STRIDENT
-+

GP12-55



Voltage & Capacity: 12V 55Ah
Dimensions mm (l x w x h): 229 x 138 x 208
Total Height mm: 213
Quantity/Ctn: 1

Terminal: Insert M6

GP12-75



Voltage & Capacity: 12V 75Ah
Dimensions mm (l x w x h): 258 x 166 x 206
Total Height mm: 215
Quantity/Ctn: 1

Terminal: Insert M6

GP12-100



Voltage & Capacity: 12V 100Ah
Dimensions mm (l x w x h): 330 x 171 x 215
Total Height mm: 220
Quantity/Ctn: 1

Terminal: Insert M6

GEL Batteries

GF12-25YG



Voltage & Capacity: 12V 28Ah
Dimensions mm (l x w x h): 197 x 132 x 180
Total Height mm: 180
Quantity/Ctn: 2

M6 Bolt & Nut

GF12-33YG2



Voltage & Capacity: 12V 38Ah
Dimensions mm (l x w x h): 210 x 175 x 175
Total Height mm: 175
Quantity/Ctn: 1

M6 Bolt & Nut

GF12-44Y



Voltage & Capacity: 12V 50Ah
Dimensions mm (l x w x h): 261 x 135 x 230
Total Height mm: 220
Quantity/Ctn: 1

Terminal: A

GF12-51Y1



Voltage & Capacity: 12V 56Ah
Dimensions mm (l x w x h): 278 x 175 x 190
Total Height mm: 190
Quantity/Ctn: 1

Terminal: A

GF12-52Y0



Voltage & Capacity: 12V 60Ah
Dimensions mm (l x w x h): 261 x 170 x 178
Total Height mm: 178
Quantity/Ctn: 1

Terminal: Insert M6

GF12-63Y0



Voltage & Capacity: 12V 70Ah
Dimensions mm (l x w x h): 261 x 171 x 210
Total Height mm: 210
Quantity/Ctn: 1

Terminal: Insert M6

GF12-94Y



Voltage & Capacity: 12V 110Ah
Dimensions mm (l x w x h): 286 x 269 x 230
Total Height mm: 230
Quantity/Ctn: 1

Terminal: A

UK central sales line:
Tel: 0845 555 55 11 | Fax: 0845 555 55 22 | sales@strident.uk.com
www.strident.uk.com

Terminal Adaptors

STRIDENT
-+

M6APL




Terminal: Auto Post
Connects to: M6 Insert
Quantity: Pair
Material: Lead Composite

M6ABL



Terminal: Auto Post
Connects to: M6 Insert
Quantity: Pair
Material: Brass

ZKKABEL552



Terminal: F1 Small Tab
Connects to: F2 Large Tab
Quantity: 10 Pairs


ZKKABEL550



Terminal: F2 Large tab
Connects to: F1 Small Tab
Quantity: 10 Pairs


Small Cell

AA



Quantity: 10
Brands may vary from those shown

AAA



Quantity: 10
Brands may vary from those shown

C



Quantity: 10
Brands may vary from those shown

PP3



Quantity: 10
Brands may vary from those shown

UK central sales line:
Tel: 0845 555 55 11 | Fax: 0845 555 55 22 | sales@strident.uk.com
www.strident.uk.com